

# Hot Stamping Foil Type B

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 01/05/2016

Date of issue: 01/05/2016

Version: 1.0

### SECTION 1: IDENTIFICATION

#### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** BW88 Sereis – Silvers and Golds

#### 1.2. Intended Use of the Product

**Use of the substance/mixture:** Hot stamping foil

#### 1.3. Name, Address, and Telephone of the Responsible Party

##### Company

Crown Roll Leaf, Inc.

91 Illinois Ave

Paterson, NJ 07503

T: 973-742-4000

#### 1.4. Emergency Telephone Number

**Emergency Number :** 973-742-4000

**Chemtrec :** 800-424-9300

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the Substance or Mixture

##### GHS-US classification

Comb. Dust

Full text of H-phrases: see section 16

#### 2.2. Label Elements

##### GHS-US Labeling

**Signal Word (GHS-US)** : Warning

**Hazard Statements (GHS-US)** : May form combustible dust concentrations in air.

#### 2.3. Other Hazards

Before processing for end use, this product is inert and poses no combustible dust hazard. When processed, machined, cut, or ground, and dust, ribbons, fines, or flakes are generated it has the potential to create a dust explosion hazard in the air. Under normal conditions of use this product has the potential to cause thermal burns. Exposure may aggravate pre-existing eye, skin, or respiratory conditions. The product involves the use of polyethylene terephthalate (PET) carrier film, on which are carried polymerized functional layers. Product has undergone polymerization, is cured and inert, and contains no unreacted monomers in the final product. This product contains components which are hazardous but are bound in a polymer matrix and are therefore not biologically available. If proper use is not followed, product has the potential to release toxic or harmful fumes/vapors. Use only as directed. Exposure to uncured diisocyanates may be harmful or cause adverse effects including but not limited to: skin, eye, and respiratory tract irritation, respiratory and skin sensitization. Uncured diisocyanates are a suspected human carcinogen, and may cause occupational asthma with repeated or prolonged exposure.

#### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product Identifier	%
Polyester Film (polyethylene terephthalate)	(CAS No) 25038-59-9	85 - 88
Polymeric Resins and Additives	(CAS No) Proprietary	8 - 31.5
Pigments and Dyes	(CAS No) Proprietary	<= 0.3
Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-)	(CAS No) 85408-46-4	<= 0.2
Silica, amorphous	(CAS No) 7631-86-9	<= 0.1
Aluminum	(CAS No) 7429-90-5	<= 0.01

Full text of H-phrases: see section 16

# Hot Stamping Foil Type B

## Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The specific chemical identity and/or exact percentage of composition has been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200]. In the event of an emergency, chemical identities and exact percentages of the proprietary ingredients may need to be disclosed to emergency personnel upon request.

### SECTION 4: FIRST AID MEASURES

#### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** Using proper respiratory protection, move the exposed person to fresh air at once. Encourage exposed person to cough, spit out, and blow nose to remove dust. Immediately call a poison center, physician, or emergency medical service.

**First-aid Measures After Skin Contact:** Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Obtain medical attention if irritation develops or persists. Cool skin rapidly with cold water after contact with molten product. Do not attempt to forcibly remove material from skin after cooling. Seek medical attention for thermal burns.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention. Removal of solidified molten material from the eyes requires medical assistance. Obtain medical attention for thermal burns.

**First-aid Measures After Ingestion:** Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Not expected to present a significant hazard under anticipated conditions of normal use. Risk of thermal burns on contact with molten product.

**Symptoms/Injuries After Inhalation:** Dust may be harmful or cause irritation. Prolonged contact with large amounts of dust may cause mechanical irritation. May cause an allergic reaction in sensitive individuals.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation. Under normal conditions of use may cause slight mechanical irritation. Dust particles generated from processing may cause an allergic reaction in sensitive individuals.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes. Eye contact with dust may cause mechanical irritation. **Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects. Gastrointestinal irritation.

**Chronic Symptoms:** None known.

#### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

### SECTION 5: FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Combustible dust. Use extinguishing media appropriate for surrounding fire.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

#### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Not considered flammable but will burn at high temperatures. Dust generated from processing may present a dust explosion hazard.

**Explosion Hazard:** Dust explosion hazard in air.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

#### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. Do not get water inside containers. Do not breathe fumes from fires or vapors from decomposition.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Risk of dust explosion.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust. Avoid generating dust. Remove ignition sources. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

##### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

# Hot Stamping Foil Type B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Ventilate area. Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

## 6.2. Environmental Precautions

Prevent entry to sewers and public waters.

## 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain solid spills with appropriate barriers and prevent migration and entry into sewers or streams. Avoid generation of dust during clean-up of spills.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Use explosion proof vacuum during cleanup, with appropriate filter. Do not mix with other materials. Vacuum clean-up is preferred. If sweeping is required use a dust suppressant. Use only non-sparking tools. Contact competent authorities after a spill.

## 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Dust generated from processing may present a dust explosion hazard. Accumulation and dispersion of dust with an ignition source can cause a combustible dust explosion. Keep dust levels to a minimum and follow applicable regulations.

**Precautions for Safe Handling:** Do not handle until all safety precautions have been read and understood. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Avoid prolonged contact with eyes, skin and clothing. Avoid breathing dust. Avoid creating or spreading dust. Keep away from heat, sparks, open flames, hot surfaces. No smoking.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Avoid creating or spreading dust. Use explosion-proof electrical, ventilating, lighting equipment. Proper grounding procedures to avoid static electricity should be followed.

**Storage Conditions:** Keep container closed when not in use. Store in a dry, cool and well-ventilated place. Store away from heat. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. **Incompatible**

**Products:** Strong acids, strong bases, strong oxidizers.

### 7.3. Specific End Use(s) Hot stamping foil

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Silica, amorphous (7631-86-9)		
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	6 mg/m <sup>3</sup>
USA IDLH	US IDLH (mg/m <sup>3</sup> )	3000 mg/m <sup>3</sup>

Aluminum (7429-90-5)		
USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup> (respirable fraction)
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable dust)
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)

# Hot Stamping Foil Type B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 8.2. Exposure Controls

**Appropriate Engineering Controls** : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits. Power equipment should be equipped with proper dust collection devices. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment. Ensure all national/local regulations are observed.

**Personal Protective Equipment** : Not generally required. The use of personal protective equipment may be necessary as conditions warrant. Gloves. Protective clothing. Protective goggles.  
Insufficient ventilation: wear respiratory protection.



**Materials for Protective Clothing** : Chemically resistant materials and fabrics.

**Hand Protection** : Wear protective gloves.

**Eye Protection** : Chemical goggles or safety glasses.

**Skin and Body Protection** : Wear suitable protective clothing.

**Respiratory Protection** : If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Thermal Hazard Protection** : When working with hot material, use suitable thermally protective clothing.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

<b>Physical State</b>	: Solid
<b>Appearance</b>	: Solid - coated film
<b>Odor</b>	: No data available
<b>Odor Threshold</b>	: No data available
<b>pH</b>	: No data available
<b>Evaporation Rate</b>	: No data available
<b>Melting Point</b>	: No data available
<b>Freezing Point</b>	: No data available
<b>Boiling Point</b>	: No data available
<b>Flash Point</b>	: No data available
<b>Auto-ignition Temperature</b>	: No data available
<b>Decomposition Temperature</b>	: No data available
<b>Flammability (solid, gas)</b>	: No data available
<b>Vapor Pressure</b>	: No data available
<b>Relative Vapor Density at 20 °C</b>	: No data available
<b>Relative Density</b>	: No data available
<b>Solubility</b>	: No data available
<b>Partition Coefficient: N-Octanol/Water</b>	: No data available
<b>Viscosity</b>	: No data available
<b>Explosive Properties</b>	: Dust generated from processing may present a dust explosion hazard.

# Hot Stamping Foil Type B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**9.2. Other Information** No additional information available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, and incompatible materials. Sparks, heat, open flame and other sources of ignition.
- 10.5. Incompatible Materials:** Strong acids, strong bases, strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates : Acrid smoke and irritating fumes. Toxic fumes. Carbon oxides (CO, CO<sub>2</sub>). Hydrocarbons. Nitrogen oxides. Amines. Hydrogen chloride. Chlorine. Ketones. Aldehydes. Formaldehyde. Formaldehyde is a potential carcinogen and can act as a potential skin and respiratory sensitizer. Formaldehyde can also cause respiratory and eye irritation. May release isocyanate vapors.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

**Acute Toxicity:** Not classified

Silica, amorphous (7631-86-9)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LC50 Inhalation Rat	> 2.2 mg/l (Exposure time: 1 h)

**Skin Corrosion/Irritation:** Not classified.

**Serious Eye Damage/Irritation:** Not classified.

**Respiratory or Skin Sensitization:** Not classified.

**Germ Cell Mutagenicity:** Not classified **Carcinogenicity:** Not classified.

Silica, amorphous (7631-86-9)	
IARC group	3

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Dust may be harmful or cause irritation. Prolonged contact with large amounts of dust may cause mechanical irritation. May cause an allergic reaction in sensitive individuals.

**Symptoms/Injuries After Skin Contact:** Prolonged exposure may cause skin irritation. Under normal conditions of use may cause slight mechanical irritation. Dust particles generated from processing may cause an allergic reaction in sensitive individuals.

**Symptoms/Injuries After Eye Contact:** May cause slight irritation to eyes. Eye contact with dust may cause mechanical irritation. **Symptoms/Injuries After Ingestion:** Ingestion may cause adverse effects. Gastrointestinal irritation. **Chronic Symptoms:** None known.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Silica, amorphous (7631-86-9)	
LC50 Fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)

# Hot Stamping Foil Type B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**12.2. Persistence and Degradability** No additional information available

**12.3. Bioaccumulative Potential** No additional information available

**12.4. Mobility in Soil** No additional information available

**12.5. Other Adverse Effects** No additional information available

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, and international regulations.

**Additional Information:** Container may remain hazardous when empty. Continue to observe all precautions.

**Ecology – Waste Materials:** Avoid release to the environment.

## SECTION 14: TRANSPORT INFORMATION

**14.1. In Accordance with DOT** Not regulated for transport

**14.2. In Accordance with IMDG** Not regulated for transport

**14.3. In Accordance with IATA** Not regulated for transport

## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

#### Polyester Film (polyethylene terephthalate) (25038-59-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Amines, C12-14-tert-alkyl, bis[2-[(4,5-dihydro-3-methyl-5-oxo-1-phenyl-1H-pyrazol-4-yl)azo]benzoato(2-)]chromate(1-) (85408-46-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Silica, amorphous (7631-86-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Aluminum (7429-90-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313

#### SARA Section 311/312 Hazard Classes

Fire hazard  
Reactive hazard

#### SARA Section 313 - Emission Reporting

1.0 % (dust or fume only)

### 15.2 US State Regulations

#### Carbon black (1333-86-4)

#### U.S. - California - Proposition 65 - Carcinogens List

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### Polymeric Resins and Additives

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

#### Silica, amorphous (7631-86-9)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

#### Aluminum (7429-90-5)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List

U.S. - Pennsylvania - RTK (Right to Know) List

# Hot Stamping Foil Type B

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Revision Date** : 01/05/2016

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

**GHS Full Text Phrases:**

Comb. Dust	Combustible Dust
Comb. Dust	May form combustible dust concentrations in air

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)